



Always be here with you!



CE

EXCAVATOR WE35



Specifications

Engine

Model	Kubota D1703 18.5KW/2200rpm
Max. Torque	97.4N.m/1500RPM
Type	In-line, water cooled, Mechanical pump, normally aspirated
Displacement	1.647L
No. of cylinder	3

Main Performance

Swing Speed (r/min)	0-11
Traveling Speed(high/low) (km/H)	4.4/2.4km/h
Grade ability (°)	58%
Max. Bucket Digging Force (kN)	30.4
Arm Digging Force (kN)	18.2
Ground Pressure (Kpa)	32
Hydraulic system pressure (Mpa)	22.5
Machine Weight (KG)	3810
Boom Length (mm)	2535
Arm Length (mm)	1400
Fuel Tank capacity (L)	42
Hydraulic Tank capacity (L)	48.5
Engine oil capacity (L)	7
Carrier roller(each side)	1
Supporting roller(each side)	4

Overall Dimensions

Overall Length (mm)	4915
Overall Width (mm)	1720
Overall Height (mm)	2525
Mini Ground clearance	295
Track width (mm)	300
Axle base (Track length on ground) (mm)	1670
Length of track (mm)	2154
Track Gauge (mm)	1420
Swing radius at tail (mm)	860
Swing radius at front (mm)	2538
Height of blade (mm)	350

Operation parameters

Bucket Capacity (m ³)	0.12
Max. Digging Radius (mm)	5480
Max. Digging Depth (mm)	3208
Max. Digging Height (mm)	4800
Max. Dumping Height (mm)	3406
Max. vertical digging depth (mm)	3208





QINGDAO ZONGJIN ENGINEERING MACHINERY CO.,LTD.

WOLF (QINGDAO) EQUIPMENT CO.,LTD.



Tel: 0086-532-66739792

Email: info@chinawheelloaders.com

WeChat/Whatsapp: +8613589171650

Address: No.88 Chunyang Rd,Chengyang,Qingdao,China