

Always be here with you!



EXCAVATOR WE10



Specifications

Engine	KD192F-1 E5
Rated power	7kw
Displacement	6.8ml/r
Bore stroke	single cylinder, fan cool
Main Performance	
Swing Speed (r/min)	0-13
Traveling Speed (km/H)	2
Grade ability (%)	30°
Traveling Tracking Force (kN)	8.3
Bucket Digging Force (kN)	7.2
Arm Digging Force (kN)	4.6
Hydraulic System	
Hydraulic system working pressure (Mpa)	16
Hydraulic Pump (Gear Pump)	Gear Pump
Hydraulic pump flow (L/min)	18
Fuel Tank Capacity (L)	26
Hydraulic Tank Capacity (L)	14.5 in Hydraulic tank
	21.5 in Hydraulic system
Overall Dimensions	
Overall Length (mm)	2840
Overall Width (mm)	880
Overall Height (mm)	2200
Counterweight Ground clearance (mm)	385
Axle Base (mm)	900
Track width (mm)	180
Undercarriage width (mm)	840
Undercarriage ground clearance (mm)	132

Operation parameters

Operation Weight (KG)	950
Bucket Capacity (m3)	0.023
Max. Digging Radius (mm)	3065
Max. Digging Depth (mm)	1715
Max. Digging Height (mm)	2600
Max. Dumping Height (mm)	1830
Tail Swing Radius(mm)	800

Advantages

- 1. Small size and easy to transport, could be loaded onto light truck or small trailer, six sets could be loaded into one 20GP container to save freight cost.
- 2. Famous brand hydraulic system parts ensure the stable quality.
- 3. Boom deflection design meet narrow work condition, reinforced rubber track to protect road
- 4. Extend hydraulic line for various attachments.
- 5. Comfort seat make operator easy to work.
- 6. Could be widely used in gardening, orchard, farming, basement reconstruction, waste residue carrying in coal washing factory, papermaking factory etc. and could replace 4~5 manpower.





QINGDAO ZONGJIN ENGINEERING MACHINERY CO.,LTD. WOLF (QINGDAO) EQUIPMENT CO.,LTD.



Tel: 0086-532-66739792

Email: info@chinawheelloaders.com WeChat/Whatsapp: +8613589171650

Address: No.88 Chunyang Rd, Chengyang, Qingdao, China