



Always be here with you!



CE

EXCAVATOR WE26



Specifications

Engine

Model	YANMAR 3TNV80F 15.2kw
RPM	2500 r/min
Type	Indirect injection (IDI). Aspiration, Natural aspiration.
Displacement	1.267 L
No. of cylinder	3

Main Performance

Swing Speed (r/min)	10.5
Traveling Speed(high/low) (km/H)	2.0/3.8km/h
Grade ability (°)	58%
Max. Bucket Digging Force (kN)	24.5
Arm Digging Force (kN)	14.8
Ground Pressure (Kpa)	31
Hydraulic system pressure (Mpa)	22
Machine Weight (KG)	2650/2700
Fuel Tank capacity (L)	35
Hydraulic Tank capacity (L)	42
Max.flow (L/min)	67.2

Overall Dimensions

Overall Length (mm)	4159
Overall Width (mm)	1500
Overall Height (mm)	2500
Mini Ground clearance	320
Track width(mm)	1550
Axle base(Track length on ground)(mm)	2040
Track Gauge(mm)	1250
Swing radius at tail(mm)	775
Swing radius at front(mm)	2096
Counterweight ground clearance(mm)	535
Turntable width (mm)	1550
Track shoe width (mm)	250

Operation parameters

Bucket Capacity(m ³)	0.08
Max. Digging Radius(mm)	4610
Max. Digging Depth(mm)	2485
Max. Digging Height(mm)	4132
Max. Dumping Height(mm)	2742
Max. vertical digging depth(mm)	2240





QINGDAO ZONGJIN ENGINEERING MACHINERY CO.,LTD.

WOLF (QINGDAO) EQUIPMENT CO.,LTD.



Tel: 0086-532-66739792

Email: info@chinawheelloaders.com

WeChat/Whatsapp: +8613589171650

Address: No.88 Chunyang Rd,Chengyang,Qingdao,China