



*Always be here with you!*



CE

# EXCAVATOR WE15



# Specifications

## Engine

Model	<b>Kubota D722 E5/EPA 10.4KW/2500rpm</b>
Max. Turque	<b>45N.m/2500RPM</b>
Type	<b>In-line, water cooled, 4 stroke, Mechanical pump, normally aspirated</b>
Displacement	<b>0.719</b>
No. of cylinder	<b>3</b>

## Main Performance

Swing Speed (r/min)	<b>12-13</b>
Traveling Speed(high/low) (km/H)	<b>2.1/3.2km/h</b>
Grade ability (°)	<b>58%</b>
Max. Bucket Digging Force (kN)	<b>9</b>
Arm Digging Force (kN)	<b>5.5</b>
Ground Pressure (Kpa)	<b>23</b>
Hydraulic system pressure (Mpa)	<b>20</b>
Machine Weight (KG)	<b>1400</b>
Fuel Tank capacity (L)	<b>14.5</b>
Hydraulic Tank capacity (L)	<b>14.5</b>
Engine oil capacity (L)	<b>3.2</b>

## Overall Dimensions

Overall Length (mm)	<b>3329</b>
Overall Width (mm)	<b>990</b>
Overall Height (mm)	<b>2267</b>
Mini Ground clearance	<b>153</b>
Track width (mm)	<b>200</b>
Axle base (Track length on ground) (mm)	<b>1190</b>
Track Gauge (mm)	<b>790(1100)</b>
Swing radius at tail (mm)	<b>655</b>
Swing radius at front (mm)	<b>1812</b>
Height of blade (mm)	<b>210</b>
Max.Dozer blade cutting (mm)	<b>229</b>
Max.Dozer blade lifting (mm)	<b>236</b>

## Operation parameters

Bucket Capacity (m <sup>3</sup> )	<b>0.025</b>
Max. Digging Radius (mm)	<b>3529</b>
Max. Digging Depth (mm)	<b>2017</b>
Max. Digging Height (mm)	<b>2955</b>
Max. Dumping Height (mm)	<b>2077</b>
Max. vertical digging depth (mm)	<b>1610</b>





QINGDAO ZONGJIN ENGINEERING MACHINERY CO.,LTD.

WOLF (QINGDAO) EQUIPMENT CO.,LTD.



Tel: 0086-532-66739792

Email: [info@chinawheelloaders.com](mailto:info@chinawheelloaders.com)

WeChat/Whatsapp: +8613589171650

Address: No.88 Chunyang Rd,Chengyang,Qingdao,China